



ROOF GUTTER AND TRACE HEATING SYSTEMS

25W/230 V | 30 W/400 V

For reliable antifreeze protection of roof gutters and downpipes: the EHC roof gutter and trace heating systems are factory-assembled, easy-to-install products that offer effective protection from damage to gutters and injury to persons from falling icicles.

TECHNICAL SPECIFICATIONS

Nominal voltage:	230/400 Volt
Output:	25/30 W/m ²
Cold tail connection:	10,00 m
Minimum installation temperature:	5 °C
Bending radius:	min. 40 mm
Resistance tolerance:	-5 % / +10 %



PRODUCT BENEFITS

- prevent cold water, drainage and heating pipes from freezing and bursting open
- prevent damage to persons, property and buildings in winter
- easy installation owing to factory-assembled components



ROOF GUTTER AND TRACE HEATING SYSTEMS

25W/230 V | 30W/400 V | 10m Cold Tail Connection



EHC Roof Gutter And Trace Heating Systems

LENGTH	OUTPUT	VOLTAGE
4,0 m	100 W	230 V
8,0 m	200 W	230 V
12,0 m	300 W	230 V
16,0 m	400 W	230 V
20,0 m	500 W	230 V
24,0 m	600 W	230 V
28,0 m	700 W	230 V
34,0 m	850 W	230 V
40,0 m	1000 W	230 V
60,0 m	1500 W	230 V
80,0 m	2000 W	230 V
100,0 m	2500 W	230 V
40,0 m	1200 W	400 V
70,0 m	1800 W	400 V
110,0 m	2400 W	400 V
140,0 m	3000 W	400 V



OTHER NEED-BASED
PRODUCTS UPON REQUEST