



# ROOF GUTTER AND TRACE HEATING SYSTEMS

25W/230 V | 30 W/400 V

For reliable antifreeze protection of roof gutters and downpipes: the EHC roof gutter and trace heating systems are factory-assembled, easy-to-install products that offer effective protection from damage to gutters and injury to persons from falling icicles.

## TECHNICAL SPECIFICATIONS

|                                   |                        |
|-----------------------------------|------------------------|
| Nominal voltage:                  | 230/400 Volt           |
| Output:                           | 25/30 W/m <sup>2</sup> |
| Cold tail connection:             | 10,00 m                |
| Minimum installation temperature: | 5 °C                   |
| Bending radius:                   | min. 40 mm             |
| Resistance tolerance:             | -5 % / +10 %           |



## PRODUCT BENEFITS

- prevent cold water, drainage and heating pipes from freezing and bursting open
- prevent damage to persons, property and buildings in winter
- easy installation owing to factory-assembled components





# ROOF GUTTER AND TRACE HEATING SYSTEMS

25W/230 V | 30W/400 V | 10m Cold Tail Connection



## EHC Roof Gutter And Trace Heating Systems

| LENGTH  | OUTPUT | VOLTAGE |
|---------|--------|---------|
| 4,0 m   | 100 W  | 230 V   |
| 8,0 m   | 200 W  | 230 V   |
| 12,0 m  | 300 W  | 230 V   |
| 16,0 m  | 400 W  | 230 V   |
| 20,0 m  | 500 W  | 230 V   |
| 24,0 m  | 600 W  | 230 V   |
| 28,0 m  | 700 W  | 230 V   |
| 34,0 m  | 850 W  | 230 V   |
| 40,0 m  | 1000 W | 230 V   |
| 60,0 m  | 1500 W | 230 V   |
| 80,0 m  | 2000 W | 230 V   |
| 100,0 m | 2500 W | 230 V   |
|         |        |         |
| 40,0 m  | 1200 W | 400 V   |
| 70,0 m  | 1800 W | 400 V   |
| 110,0 m | 2400 W | 400 V   |
| 140,0 m | 3000 W | 400 V   |



OTHER NEED-BASED  
PRODUCTS UPON REQUEST